



## UNIQUE DESIGN FEATURES

- \* Cost effective containerisation
- \* Quick set-up
- \* Process connection flexibility
- \* Level Gauging
- \* Environmentally friendly



## Standard Features

### Nom. Capacity

65,000 ltr (17,195 USgal)  
 28,000 ltr (7,410 USgal)  
 10,000 ltr (2,645 USgal)

### Tare (nom)

10,000 kg  
 7,000 kg  
 4,000 kg

### Dimensions

40ft x 8ft x 9ft 6"  
 20ft x 8ft x 8ft 6"  
 10ft x 8ft x 8ft 6"



Fit your equipment here behind secure lockable doors.

- Pumps
- Meters
- Dispensers

## Standard Equipment

(Valves and Pipes are ASTM - 5 Bar)

Manways:

2 x 600mm Diameter

Venting:

4" Vent stack

Discharge Valve:

High level to low - 3" fill connection.

Generator connections:

High level 1" for supply 2 x Generators.

Dispenser Valve:

High level to low - 2" for connection to pump or dispenser

Overfill Protection:

3" Overfill valve

Height Access:

Ladder or walkway options—hand rail at height

### Tectainer Products Inc:

Bulk Containers

20ft and 40ft Full Opening Side Door Containers

Waste-management Containers

Open-top, GPs & Flatracks

LPG T50 tanks

27 tonne Bitumen tanks

28,000 ltr Lubricant & Oil Tanks

70 m3 Petrochem storage Tanks

26,000 ltr tank containers

28,000 ltr Food tanks

