



UNIQUE DESIGN FEATURES

- * Patented Frame Design
- * Stress free frame
- * High Expansion capability
- * Dynamic Test 8g
- * Crash protection
- * Modular construction
- * Ease of maintenance

Standard Features

<u>Nom. Capacity</u>	<u>Tare</u>	<u>MGW</u>
26,000 ltr (6869 USgal)	3,950 kg (8706 lb)	36,000 kg (79344 lb)
24,000 ltr (6340 USgal)	3,820 kg (8419 lb)	35,000 kg (77140 lb)
22,000 ltr (5812 USgal)	3,710 kg (8177 lb)	34,000 kg (74936 lb)
Working Pressure:	4 bar (58 psi)	0.41 bar allowable vacuum
Test Pressure:	6 Bar (87 psi)	<i>(NB: 2.65 bar tanks also avail.)</i>
ISO Dimensions:	L6058mm x W2048mm x H2591mm (20' x 8' x 8' 6")	
Structural Materials:	EN 10210, EN10025, SS 316L	
Insulation System:	Rockwool with Alum mech. protection	
Approvals:	UN coded T11, RID/ADR, USDOT, AAR 600, UIC, TIR	

Standard Equipment (Fortvale or Customers Choice)

Manway:	500mm Dia.
Pressure Device:	2 1/2" Prevac (+ spares)
Air Inlet:	1 1/2" Ball valve (+ spares)
Discharge Valve:	3" High-flow double closure valve
Calibration:	Charted
High Access:	Ladder, walkways and hand rail
Ancillary Equip:	Doc. holders & remote cable

Tectainer Products Inc:

Bulk Containers

20ft and 40ft Full Opening Side Door Containers

Waste-management Containers

Open-top, GPs & Flatracks

LPG T50 tanks

27 tonne Bitumen tanks

28,000 ltr Lubricant & Oil Tanks

70 m3 Petrochem storage Tanks

26,000 ltr tank containers

28,000 ltr Food tanks

