# **Dangerous Goods Stores**

General Information										
Unit	Storage	Largest	Tare							
	Volume	Package	Weight							
6 Foot	1500 L	210 L	980 kg							
8 Foot	3100 L	210 L	1350 kg							
10 Foot	4500 L	210 L	1510 kg							



www.tectainer.co.uk

### **Tectainer** Products Inc:

**Bulk Containers** 

20ft and 40ft Full Opening Side Door Containers

Waste-Management Containers

Open-top, GPs & Flatracks

LPG T50 Tanks

27 tonne Bitumen tanks

28.000 Ltr Lubricant & Oil Tanks

70m3 Petrochem storage Tanks

26,000 ltr tank containers

28.000 ltr Food tanks

	Unit	External		Internal Door		Standing	
		Height	Width	Depth	Height	Width	Height
	6 Foot	1.990 m	1.960 m	1.83 m	1.62 m	1.866 m	1.73 m
	8 Foot	2.445 m	2.200 m	2.438 m	2.04 m	2.106 m	2.15 m
	10 Foot	2.896 m	2.438 m	2.991 m	2.495 m	2.342 m	2.605 m

Physical Dimensions

# **UNIQUE DESIGN FEATURES**

- Strong shipping container construction.
- 10ft unit is CSC plated for shipping.
- Reasonable standing height in smallest 6ft unit.
- Anti spark, Anti slip floor.
- Emergency Exit locking system.
- Side hatch to allow fuel line and power cable feeds, etc.
- Secure Lock-box.
- Ideal Generator Houses.





### **HEAD OFFICE**

**TEC-Armech UK Limited** Haywards Heath, W. Sussex UK. Tel: +44 (0) 1444 230 865 Fax: +44 (0) 1444 230 885

WORLDWIDE OFFICES: TEC-Armech (Mechanical) Ltd, Shanghai, China. Armech Mechanical Ltd. Auckland. New Zealand. Armech Europe SARL, Annecy, France. Container Options Pty, Sydney, Australia.

**JV FACTORY** Armech (Mechanical) Ltd Yixing, Jiangsu Province PR China.



## **Specification**

- Designed & built for Class 3 products to AS 1940 2004, AS1692 - 2006, BS799 Part 5, & BS 7959
- Stacked 10ft units joined & shipped as a 20ft ISO.
- 4 large ventilation grills at roof & floor level enhance cross air flow, minimise toxic fumes build up and reduce inside temperature.
- Double Safe Drain Valve fitted to floor sump.
- Double door access with key lock security.
- · Painted yellow for distinctive visibility.
- · Fork lift pockets for ease of movement.



